

Supports 100 site-to-site BOVPN tunnels, 4×2.5Gb + 4×1Gb ports, and enterprise-grade security in a compact design.



## Secure Performance for Small Branch Offices

Designed for small sites and remote offices, the Firebox M295 delivers 1.8 Gbps UTM throughput, 1.12 Gbps HTTPS inspection, and support for up to 100 users. With a compact design and flexible port options, it's the right choice for organizations needing enterprisegrade security in a cost-conscious package.

WatchGuard Network Security has been my go to solution for firewalls and WAN security for many years. I like the scalability of the devices and the licensing options. I appreciate the different licensing options for the solutions including the different add on services for increased security offerings like botnet scanning, IPS, gateway a/v, etc.

~Mike Broseus


IT Manager, Advanced Business Communications Inc

Firebox M295	Technical Specifications		
Throughput <sup>1</sup>			
UTM (full scan) <sup>2</sup>	1.85 Gbps		
VPN (IMIX)	1.80 Gbps		
HTTPS (IPS enabled, full scan)	1.12 Gbps		
Antivirus	3.00 Gbps		
IPS (full scan)	2.41 Gbps		
Firewall (UDP 1518)	7.90 Gbps		
VPN (UDP 1518)	5.80 Gbps		
Capacity			
Network Interfaces	4x2.5Gb, 4x1Gb, 2xSFP+		
I/O interfaces	1 Serial/2 USB-A 3.2		
Concurrent connections	6,000,000		
Concurrent connections (proxy)	320,000		
New connections per second	N/A		
VLANs	Unrestricted		
WSM licenses (incl)	4		
EDR Core Sensors included	75		
VPN Tunnels			
Branch Office VPN	100		
Mobile VPN	100		
Electrical	Obtained and the second in TLO description arrange frame.		
Firewall	Stateful packet inspection, TLS decryption, proxy firewall		
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS, and Explicit Proxy		
Threat protection	DoS attacks, fragmented & malformed packets, blended threats		
Filtering options	Browser Safe Search, Google for Business		
VPN			
Site to Site VPN	KEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke		
Remote Access VPN	IKEv2, IPSec, L2TP, TLS		
Visibility			
Logging and notifications	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3		
Reporting	WatchGuard Cloud includes over 100 pre-defined reports, executive summary, and visibility tools		

Firebox M295	Technical Specifications		
Certifications			
Security	Pending: CC, FIPS 140-3		
Safety	NRTL/CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, RoHS, REACH		
Networking			
SD-WAN	Multi-wan failover, dynamic path selection, jitter/loss/latency measurement		
Dynamic Routing	RIP, OSPF, BGP		
High Availability	Active/Passive, Active/Active		
QoS	802.1Q, DSCP, IP Precedence		
Traffic Management	By policy or application		
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
NAT	Static, dynamic, 1:1, IPSec traversal, policy- based		
Link aggregation	802.3ad dynamic, static, active/backup		

Physical and Power Specifications				
Product Dimensions	17.24" x 12.60" x 1.73"			
Product Differsions	(438 x 320 x 44 mm)			
Chinning Dimension	22" x 21" x 5.25"			
Shipping Dimension	(558.8 x 533.4 x 185.85 mm)			
Product Weight	7.72 lbs			
Product Weight	3.5 kg			
Shipping Weight	<b>/eight</b> 13.75 lbs (6.25 kg)			
Power Consumption	38.4 W (Max)			
Power	1x C14 inlet (90-264VAC)			

Environment	Operating	Storage
Temperature	32° F to 104° F 0° C to 40° C	14° to 158° F -10° to 70° C
Relative Humidity	5% to 90% non-condensing	5% to 90% non-condensing
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)
MTBF	169,178 hours	



## **Strong Security at Every Layer**

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses against advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing, and much more.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard. com/sizing to access the online Product Sizing Tool.

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

	Standard Support	Basic Security	Total Security
Stateful Firewall	✓	/	✓
VPN	✓	✓	✓
SD-WAN	✓	✓	✓
Access Portal*	✓	/	✓
Intrusion Prevention Service (IPS)		✓	✓
Application Control		✓	✓
WebBlocker		✓	✓
spamBlocker		✓	✓
Gateway AntiVirus		✓	✓
Reputation Enabled Defense		✓	✓
Network Discovery		✓	✓
APT Blocker			✓
DNSWatch			✓
IntelligentAV*			✓
ThreatSync (XDR)			✓
EDR Core			✓
WatchGuard Cloud Log Data Retention Report Data Retention		90 Days 1 Day	365 Days 30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)
thick continues on Cirches T115 W T05 (T05 W co.)	TOE D		

\*Not available on Firebox T115-W, T25/T25-W, or T35-R.
Total Security Suite required for M295, M395, M495, M595, M695, FireboxV and Firebox Cloud.

<sup>&</sup>lt;sup>1</sup>Throughput rates are determined using multiple flows through multiple ports and will vary depending on the environment and configuration. Max firewall throughput tested via direct connection using 1518-byte UDP frames based on RFC 2544 methodology. All testing performed on Fireware version 2025.1.

 $<sup>^{\</sup>rm 2}$  UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on