

Firebox M395

Features multi-gig ports for higher throughput, SD-WAN, and high availability (HA). Ideal for scaling network environments.



Scalable Security for Growing Networks

Built for midsize environments, the Firebox M395 offers 3.8 Gbps UTM performance, 1.9 Gbps HTTPS inspection, and support for up to 250 users. It's engineered to scale with your business while maintaining reliable protection against advanced threats.

WatchGuard Network Security has been my go to solution for firewalls and WAN security for many years. I like the scalability of the devices and the licensing options. I appreciate the different licensing options for the solutions including the different add on services for increased security offerings like botnet scanning, IPS, gateway a/v, etc.

~Mike Broseus

IT Manager, Advanced Business Communications Inc

Firebox M395	Technical Specifications	
Throughput ¹		
UTM (full scan) ²	3.00 Gbps	
VPN (IMIX)	2.55 Gbps	
HTTPS (IPS enabled, full scan)	1.90 Gbps	
Antivirus	5.90 Gbps	
IPS (full scan)	4.50 Gbps	
Firewall (UDP 1518)	20.00 Gbps	
VPN (UDP 1518)	8.10 Gbps	
Capacity		
Network Interfaces	2.5 Gbps RJ45 x 12, 1 Gbps SFP x 2, 10 Gbps SFP+ x 2	
I/O interfaces	1 Serial/2 USB-A 3.2	
Concurrent connections	6,000,000	
Concurrent connections (proxy)	320,000	
New connections per second	N/A	
VLANs	Unrestricted	
WSM licenses (incl)	4	
EDR Core Sensors included	150	
VPN Tunnels		
Branch Office VPN	350	
Mobile VPN	350	
Firewall	Stateful pooket inapportion TLS degreption prove firewall	
	Stateful packet inspection, TLS decryption, proxy firewall	
Application proxies	HTTP, HTTPS, FTP, DNS, TCP/UDP, POP3S, SMTPS, IMAPS, and Explicit Proxy	
Threat protection	DoS attacks, fragmented & malformed packets, blended threats	
Filtering options	Browser Safe Search, Google for Business	
VPN		
Site to Site VPN	KEv2, IPSec, Policy and Route Based Tunnels, TLS hub and spoke	
Remote Access VPN	IKEv2, IPSec, L2TP, TLS	
Visibility		
Logging and notifications	WatchGuard Cloud & Dimension, Syslog, SNMP v2/v3	
Reporting	WatchGuard Cloud includes over 100 pre-defined reports, executive summary, and visibility tools	


Firebox M395	Technical Specifications		
Certifications			
Security	Pending: CC, FIPS 140-3		
Safety	NRTL/CB		
Network	IPv6 Ready Gold (routing)		
Hazardous substance control	WEEE, RoHS, REACH		
Networking			
SD-WAN	Multi-wan failover, dynamic path selection, jitter/loss/latency measurement		
Dynamic Routing	RIP, OSPF, BGP		
High Availability	Active/Passive, Active/Active		
QoS	802.1Q, DSCP, IP Precedence		
Traffic Management	By policy or application		
IP address assignment	Static, DHCP (server, client, relay), PPPoE, DynDNS		
NAT	Static, dynamic, 1:1, IPSec traversal, policy-		

Physical and Power Specifications				
Product Dimensions	17.3" x 12.2" x 1.73"			
	(440 x 310 x 44 mm)			
Shipping Dimension	21.75" x 20" x 5.25"			
Shipping Dimension	(552.45 x 508 x 185.85 mm)			
Product Weight	10.8 lbs (4.90 kg)			
Shipping Weight	14.05 lbs (6.4 kg)			
Power Consumption	102 W (Max)			
Power	1x C14 inlet (90-264VAC)			
ruwei	1x CRPS slot (optional)"			

based

802.3ad dynamic, static, active/backup

Environment	Operating	Storage
Temperature	32° F to 104° F 0° C to 40° C	14° to 158° F -10° to 70° C
Relative Humidity	5% to 90% non-condensing	5% to 90% non-condensing
Altitude	0 to 9,843 ft at 95° F (3,000 m at 35° C)	0 to 15,000 ft at 95° F (4,570 m at 35° C)
MTBF	324,136 hours	



Strong Security at Every Layer

NAT

Link aggregation

Uniquely architected to be the industry's smartest, fastest, and most effective network security products, WatchGuard solutions deliver in-depth defenses again advanced malware, ransomware, botnets, trojans, viruses, drive-by downloads, data loss, phishing, and much more.

Contact your WatchGuard reseller or call WatchGuard directly (1.800.734.9905) for help determining the right model for your network. Visit www.watchguard.com/sizing to access the online Product Sizing Tool.

For details, talk to your authorized WatchGuard reseller or visit www.watchguard.com.

	Standard Support	Basic Security	Total Security
Stateful Firewall	✓	/	✓
VPN	✓	✓	✓
SD-WAN	✓	✓	✓
Access Portal*	✓	✓	✓
Intrusion Prevention Service (IPS)		✓	✓
Application Control		✓	✓
WebBlocker		✓	✓
spamBlocker		✓	✓
Gateway AntiVirus		✓	✓
Reputation Enabled Defense		✓	✓
Network Discovery		✓	✓
APT Blocker			✓
DNSWatch			✓
IntelligentAV*			✓
ThreatSync (XDR)			✓
EDR Core			✓
WatchGuard Cloud Log Data Retention Report Data Retention		90 Days 1 Day	365 Days 30 Days
Support	Standard (24 x 7)	Standard (24 x 7)	Gold (24 x 7)

^{*}Not available on Firebox T115-W, T25/T25-W, or T35-R. Total Security Suite required for M295, M395, M495, M595, M695, FireboxV and Firebox Cloud

¹Throughput rates are determined using multiple flows through multiple ports and will vary depending on the environment and configuration. Max firewall throughput tested via direct connection using 1518-byte UDP frames based on RFC 2544 methodology. All testing performed on Fireware version 2015.

² UTM throughput is measured using HTTP traffic with AV, IPS, and Application Control enabled, and does not account for all security services available on the appliance.